


# Pneumatic Quick Couplings



## C Type









(Small Body, Chrome-plated steel)

### Single Open and Close Pneumatic Quick Couplings



Socket with valve Plug without valve

Description: It is widely used in Asian market.  
 Features: Simple structure, various of connections.  
 Application: Pneumatic tools, automotive, compressed air, shipbuilding.  
 Compatibility: Nitto HI-CUPLA series, CEJN 315 series, Rectus 13KA series.  
 Working Pressure: 1.0 Mpa Working Temperature: -20°C to +100°C



Part No .	LS	φD	Hs	A	φT	d
C-10SH	60	24	21	26	7	3.5
C-20SH	60	24	21	26	9	5
C-30SH	61.5	24	21	28	11.2	7.3
C-40SH	67.5	24	21	33	14	9

Part No .	LS	φD	Hs	A	T(BSP)	d
C-10SF	43	24	21	12	BSP1/8"	8
C-20SF	45	24	21	13	BSP1/4"	8
C-30SF	45	24	21	15	BSP3/8"	8
C-40SF	48	24	21	16	BSP1/2"	8

Part No .	LS	φD	Hs	A	T(PT)	d
C-10SM	54	24	21	10	PT1/8"	5
C-20SM	48	24	21	13	PT1/4"	8
C-30SM	48	24	21	13	PT3/8"	10.5
C-40SM	50	24	21	14	PT1/2"	13.5

Part No .	LS	φD	Hs	A	T	d
C-10SP	47	24	21	13	6*4	3
C-20SP	48	24	21	14	8*5	4
C-30SP	49	24	21	16.5	10*6.5	5
C-40SP	51	24	21	18.5	12*8	6

Part No .	Lp	C	Hp	A	φT	d
C-10PH	56	20.5	φ15	28	7	7.5
C-20PH	56	20.5	φ15	30	9	7.5
C-30PH	56	20.5	φ15	30	11.2	7.5
C-40PH	56	20.5	φ18	33	13.5	7.5

Part No .	Lp	C	Hp	A	T(BSP)	d
C-10PF	34.5	20.5	14	12	BSP1/8"	7.5
C-20PF	37.5	20.5	17	15	BSP1/4"	7.5
C-30PF	37.5	20.5	21	15	BSP3/8"	7.5
C-40PF	38.5	20.5	24	16	BSP1/2"	7.5

Part No .	Lp	C	Hp	A	T(PT)	d
C-10PM	37	20.5	14	10	PT1/8"	7.5
C-20PM	40	20.5	14	13	PT1/4"	7.5
C-30PM	40	20.5	17	13	PT3/8"	7.5
C-40PM	44	20.5	22	15	PT1/2"	7.5

Part No .	Lp	C	Hp	A	T	d
C-10PP	36.5	20.5	14	13	6*4	3
C-20PP	41	20.5	14	14	8*5	4
C-30PP	44	20.5	16	16.5	10*6.5	5
C-40PP	48	20.5	19	18.5	12*8	6