

Pneumatic Quick Couplings



NA Type









(Nickel-plated steel)

Single Hand Self-locking Pneumatic Quick Couplings



Description: It is widely used in Asia market.
 Features: Simple structure,multiple connection can be alternative.
 Application: Pneumatic tools,automotive,compressed air,shipbuilding.
 Compatibility: Nitto HI-CUPLA series,CEJN 315series,Rectus 13KA series.
 Working Pressure:1.5 Mpa Working Temperature:-20°C to +100°C

- Double seal
- Nipples heat treatment



Part No .	LS	φD	Hs	A	φT	d
NA-10SH	72.5	27	22	25	7	3.5
NA-20SH	74.5	27	22	25	9	5
NA-30SH	74.5	27	22	25	11.2	7.3
NA-40SH	77.5	27	22	25	14.5	9

Part No .	LS	φD	Hs	A	T(BSP)	d
NA-10SF	54	27	22	12	BSP1/8"	8
NA-20SF	57	27	22	13	BSP1/4"	8
NA-30SF	57	27	22	15	BSP3/8"	8
NA-40SF	59	27	22	16	BSP1/2"	8

Part No .	LS	φD	Hs	A	T(PT)	d
NA-10SM	55.5	27	22	10	PT1/8"	5
NA-20SM	58.5	27	22	13	PT1/4"	8
NA-30SM	58.5	27	22	15	PT3/8"	10.5
NA-40SM	60.5	27	22	16	PT1/2"	13.5

Part No .	LS	φD	Hs	A	T	d
NA-10SP	55	27	22	13	6*4	3
NA-20SP	59.5	27	22	14	8*5	4
NA-30SP	59.5	27	22	16.5	10*6.5	5
NA-40SP	62.5	27	22	18.5	12*8	6

Part No .	Lp	C	Hp	A	φ T	d
NA-10PH	57	20.5	φ15	28	7	7.5
NA-20PH	57	20.5	φ15	30	9	7.5
NA-30PH	57	20.5	φ15	30	11.2	7.5
NA-40PH	57	20.5	φ18	33	15	7.5

Part No .	Lp	C	Hp	A	T(BSP)	d
NA-10PF	34.5	20.5	14	12	BSP1/8"	7.5
NA-20PF	37.5	20.5	17	15	BSP1/4"	7.5
NA-30PF	37.5	20.5	21	15	BSP3/8"	7.5
NA-40PF	38.5	20.5	24	16	BSP1/2"	7.5

Part No .	Lp	C	Hp	A	T(PT)	d
NA-10PM	37	20.5	14	10	PT1/8"	7.5
NA-20PM	40	20.5	14	11	PT1/4"	7.5
NA-30PM	40	20.5	17	13	PT3/8"	7.5
NA-40PM	44	20.5	22	15	PT1/2"	7.5

Part No .	Lp	C	Hp	A	T	d
NA-10PP	36.5	20.5	14	13	4*6	3
NA-20PP	41	20.5	14	14	5*8	4
NA-30PP	44	20.5	16	16	6.5*10	5
NA-40PP	48	20.5	19	19	8*12	6