


Pneumatic Quick Couplings












SUS type (Large body, 304 Stainless Steel)

Single Open and Close Pneumatic Quick Couplings



Description: It is widely used in Asia market.
 Features: Simple structure, multiple connection can be alternative.
 Application: Pneumatic tools, automotive, compressed air, shipbuilding.
 Compatibility: Nitto HI-CUPLA series, CEJN 315 series, Rectus 13KA series.
 Working Pressure: 1.0Mpa Working Temperature: -20°C to +100°C



Part No .	LS	φD	Hs	A	φT	d
MS-10SH	72.5	26	21	28	7	3.5
MS-20SH	72.5	26	21	30	9	5
MS-30SH	72.5	26	21	30	11.2	7.3
MS-40SH	75.5	26	21	33	14.5	9

Part No .	LS	φD	Hs	A	T(BSP)	d
MS-10SF	49.5	26	21	12	BSP1/8"	8
MS-20SF	49.5	26	21	13	BSP1/4"	8
MS-30SF	50.5	26	21	15	BSP3/8"	8
MS-40SF	55.5	26	21	16	BSP1/2"	8

Part No .	LS	φD	Hs	A	T(PT)	d
MS-10SM	54	26	21	10	PT1/8"	5
MS-20SM	55.5	26	21	13	PT1/4"	8
MS-30SM	55.5	26	21	13	PT3/8"	10.5
MS-40SM	57.5	26	21	14	PT1/2"	13.5

Part No .	LS	φD	Hs	A	T	d
MS-10SP	55	26	21	13	6*4	3
MS-20SP	56.5	26	21	14	8*5	4
MS-30SP	57.5	26	21	16.5	10*6.5	5
MS-40SP	60.5	26	21	18.5	12*8	6

Part No .	Lp	C	Hp	A	φT	d
MS-10PH	56	20.5	φ15	28	7	7.5
MS-20PH	56	20.5	φ15	30	9	7.5
MS-30PH	56	20.5	φ15	30	11.2	7.5
MS-40PH	56	20.5	φ18	33	13.5	7.5

Part No .	Lp	C	Hp	A	T(BSP)	d
MS-10PF	34.5	20.5	14	12	BSP1/8"	7.5
MS-20PF	37.5	20.5	17	15	BSP1/4"	7.5
MS-30PF	37.5	20.5	21	15	BSP3/8"	7.5
MS-40PF	38.5	20.5	24	16	BSP1/2"	7.5

Part No .	Lp	C	Hp	A	T(PT)	d
MS-10PM	37	20.5	14	10	PT1/8"	7.5
MS-20PM	40	20.5	14	13	PT1/4"	7.5
MS-30PM	40	20.5	17	13	PT3/8"	7.5
MS-40PM	44	20.5	22	15	PT1/2"	7.5

Part No .	Lp	C	Hp	A	T	d
MS-10PP	36.5	20.5	14	13	6*4	3
MS-20PP	41	20.5	14	14	8*5	4
MS-30PP	44	20.5	16	16.5	10*6.5	5
MS-40PP	48	20.5	19	18.5	12*8	6