

MVF90D Series

SPECIFICATION

Max. Vacuum level	: -92Kpa(-690mmHg)
Supply Air pressure	: 4 - 6bar, Max. 6.5bar
Supply Air type	: Dry Compressed Air
Working temperature range	: -20°C to +80°C
Noise level	: 50-60dBA
Material	: AL, ABS, Glass Filled Nylon
Sealing Material	: NBR(standard) Option: silicon, viton



CHARACTERISTIC

Model	Max.vacuum -Kpa(-mmHg)	Max.vacuum flow (L/min)	Air consumption (L/min)	Capacity equivalent to electricity motor pump size
MVF90D-20	92(690)	568	150 - 188	0.5 kw
MVF90D-30	92(690)	852	225 - 282	0.75 kw
MVF90D-40	92(690)	1100	300 - 376	1 kw
MVF90D-50	92(690)	1349	375 - 470	1.25 kw
MVF90D-60	92(690)	1527	450 - 564	1.5 kw

DIMENSIONAL INFORMATION

Model	Size(mm)				
	L	W	T	H	B
MVF90D-20	194	80	43	166	159
MVF90D-30	194	80	43	166	159
MVF90D-40	194	80	64	187	159
MVF90D-50	194	80	64	187	159
MVF90D-60	194	80	64	187	159

- Accessories**

 - Vacuum Gauge 1pcs
 - Silencer 2pcs
 - Bracket 2pcs
 - Bolt 2pcs

- ① Compressed Air G1/4"
- ② Vacuum G3/4"
- ③ Vacuum G3/8"
- ④ Exhaust G3/4"

